

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-14 (cancelled)

Sub 27
D2
Claim 15 (currently amended) A method to increase throughput of a recovery boiler applicable to boilers with at least three air injection levels, the three levels being primary, secondary and tertiary air injection levels, ~~or boilers that originally had two air injection levels that have been retrofitted with a third air injection level~~, the method comprising injecting oxygen at least at the secondary and the tertiary air injection levels, wherein the ratio of total oxygen to total combustion air at any air injection level is the oxygen enrichment concentration for that air injection level.

✓
Claim 16 (cancelled)

Claim 17 (currently amended) Method in accordance with claim 15 wherein the recovery boiler has the same oxygen enrichment concentration in the secondary and tertiary air injection levels, the oxygen enrichment concentrations being greater than 21%.

Claim 18 (original) Method in accordance with claim 15 wherein the recovery boiler has different oxygen enrichment concentrations in each air injection level, and the oxygen enrichment concentrations being greater than 21% in each air injection level.

Sub 27
D2
Claim 19 (currently amended) A method of increasing throughput of a recovery boiler applicable to boilers with at least four air injection levels, the four levels being primary, secondary, ~~third~~ tertiary and ~~fourth~~ quaternary air injection levels, the method comprising applying oxygen enrichment to the secondary air injection level and to one or more of ~~third~~ tertiary and ~~fourth~~ quaternary air injection levels, wherein the ratio of total oxygen to total combustion air at any air injection level is the oxygen enrichment concentration for that air injection level.

Claim 20 (currently amended) Method in accordance with claim 19 wherein oxygen is injected at the primary air injection level in addition to the secondary and ~~fourth~~ quaternary air injection levels.

Claim 21 (original) Method in accordance with claim 19 wherein the recovery boiler has the same oxygen enrichment concentrations in the primary, secondary and tertiary air injection levels, the oxygen enrichment concentrations being greater than 21%.

Claim 22 (original) Method in accordance with claim 19 wherein the recovery boiler has different oxygen enrichment concentrations in each air injection level, the oxygen enrichment concentrations being greater than 21% in each air injection level.

10/27
Claim 23 (original) Method in accordance with claim 19 wherein the recovery boiler has oxygen enrichment concentrations being greater than 21% and up to 30% in one or more of the primary, secondary, and tertiary air injection levels.

D2
Claim 24 (currently amended) Method in accordance with claim 19 wherein the recovery boiler has oxygen enrichment concentrations being greater than 21% and up to 30% in one or more of the primary, secondary, and ~~third~~ tertiary and ~~fourth~~ quaternary air injection levels.

Claim 25 (currently amended) A method of controlling the oxygen concentration in the flue gas of a recovery boiler, the method being applicable to boilers with at least three levels of air injection, ~~or a recovery boiler with an original two-level air injection system retrofitted to three air injection levels~~, the method including the steps of:

- a) supplying oxygen flows to at least two air injection levels of the recovery boiler, the two air injection levels being different from the primary air injection level, for oxygen enrichment of the two air injection levels;

- Pub 07
- D2
- b) generating a flue gas by burning black liquor in a combustion zone of the recovery boiler;
 - c) selecting a set point oxygen concentration;
 - d) sensing the oxygen concentration in the flue gas;
 - e) adjusting the oxygen flow injected in the tertiary air injection level, in order to maintain the sensed oxygen concentration at ~~about~~ the set point oxygen concentration, while maintaining the flow of oxygen in the secondary air injection level constant.

Claim 26 (currently amended) A method of controlling the oxygen concentration in the flue gas of a recovery boiler, the method being applicable to boilers with ~~at least~~ four levels of air injection, the method comprising the steps of:

- a) supplying oxygen flows to ~~at least~~ two air injection levels of the recovery boiler, the two air injection levels being different from the primary air injection level, for oxygen enrichment of the two air injection levels;
- b) generating a flue gas by burning black liquor in a combustion zone of the recovery boiler;
- c) selecting a desired set point oxygen concentration;
- d) sensing the oxygen concentration in the flue gas;
- e) adjusting the oxygen flow injected in the uppermost air injection level, in order to maintain the sensed oxygen concentration at ~~about~~ the set

Sub 27
point oxygen concentration, while maintaining the flow of oxygen in the other air injection level constant.

Claim 27 (currently amended) A method to improve the combustion stability of a recovery boiler comprising the steps of:

- D2
- a) supplying oxygen flows to ~~the~~ a primary air injection level of the recovery boiler for oxygen enrichment of the primary air;
 - b) generating a flue gas by burning black liquor in a combustion zone of the recovery boiler;
 - c) sensing ~~the~~ a sulfur dioxide concentration in the flue gas;
 - d) adjusting the oxygen flow ~~injected in~~ supplied to the primary air injection level in order to minimize the sulfur dioxide ~~emissions~~ concentration.

Claim 28 (currently amended) A method to improve the combustion stability of a recovery boiler comprising the steps of:

- a) supplying oxygen flows to a secondary air injection level of the recovery boiler for oxygen enrichment of the primary air; wherein the ratio of total oxygen to total combustion air at any air injection level is the oxygen enrichment concentration for that air injection level;
- b) generating a flue gas by burning black liquor in a combustion zone of the recovery boiler;

- Sub 27
- c) sensing ~~the~~ a sulfur dioxide concentration in the flue gas resulting from the combustion of said oxygen enrichment;
 - d) adjusting the oxygen flow ~~injected in~~ supplied to the secondary air injection level, in order to minimize the sulfur dioxide ~~emissions~~ concentration.

Claim 29 (original) Method in accordance with claim 28 wherein the oxygen enrichment concentration in each air injection level is controlled independently.

Sub 28

Claim 30 (currently amended) A method of controlling the temperature profile in a recovery boiler, the method including the steps of:

- a) supplying oxygen flows to ~~at least~~ two air injection levels of the recovery boiler, the two air injection levels being different from the primary air injection level, for oxygen enrichment of the two air injection levels;
- b) burning black liquor in a combustion zone of the recovery boiler;
- c) selecting a boiler set point temperature profile;
- d) sensing average temperatures at different ~~levels of~~ heights in the boiler with an optical technique, and inferring a temperature profile to the boiler, adjusting the oxygen flow injected in the at least two air injection levels so that the ~~measured~~ temperature profile matches the boiler set point temperature profile.

Claims 31-33 (cancelled)